

POLYSTER FILTER (SIDE 750-900)

COMBINATION OF QUALITY AND ELEGANCE
For residential and semi-commercial pools




PRODUCT FEATURES

Product Features:

- Tank Material: Gelcoat Fiberglass
- Max operating pressure 36 psi / 2.5 bar
- Max temperature of 43°C (109°F)
- 6-way multiport valve (1.5"MPV03, 2"MPV04)
- ABS lateral system
- Pressure gauge
- Universal standard of union connection
- Piping kit



For residential and semi-commercial pools



USER - FRIENDLY AND INNOVATIVE DESIGN

Aqua Pool Group Gelcoat Filters are produced by skilled workers and experienced engineers in modern manufacturing facilities. Each product is subject to a %100 inspection at every production stage and a strict hydrostatic pressure test. In order to achieve their best performance, 20,000 cycle tests were conducted to determine the specifications of the filters.

Model	Dia,mm	Area,m ²	Max.Flow Rate,LPM	Max. Working Pressure, bar	Max. Temperature, °c	Sand,kg	Valve Size,Inch
APT 550	530	0.22	11.10	2.5	≤ 40	85	1.5
APT 650	640	0.32	15.60	2.5	≤ 40	145	1.5
APT 750	750	0.44	23.00	2.5	≤ 40	230	2
APT 900	900	0.64	31.20	2.5	≤ 40	470	2
APS 550	530	0.22	11.10	2.5	≤ 40	85	1.5
APS 650	640	0.32	15.60	2.5	≤ 40	145	1.5
APS 750	750	0.44	23.00	2.5	≤ 40	230	2
APS 900	900	0.64	29.70	2.5	≤ 40	470	2